

# A Detailed Study of Channel Estimation and BER Optimization in presence of AWGN and Rayleigh Channel of OFDM System

Santosh, Piyush Vyas

M.Tech. Scholar, Electronics & Communication, Jodhpur Institute of Engineering and Technology, Jodhpur, India  
santukhurchuriya@gmail.com

Associate Professor, Electronics & Communication, Jodhpur Institute of Engineering and Technology, Jodhpur, India  
piyush.vyas@jietjodhpur.ac.in

**Abstract**—Orthogonal Frequency Division Multiplexing is an important one field communication and that uses parallel information series. Contrast and single carrier adjustment are basic aspects of this technique where OFDM has many favourable circumstances are risky to work on this technique. It is robust, easy to use, and strength to save the processing channel from distortions. It provides safety from multipath, much lesser computational many-sided characteristic. OFDM has some significant to execute it in commonly using media transmission frameworks. OFDM standard tolerate Packet misfortune, Bit trouble, Bit Error Rate (BER), Signal to Noise Ratio (SNR), Calculation of PAPR, Power Spectrum estimation. This dissertation is targeted to show the comparison of AWGN and Rayleigh channel by using fading process for particularity in superior performance with individual values of spectrums as well as by their scattering plots. In this dissertation each and every signal of these terms are examined and all the four parameters are thought about utilizing AWGN and Rayleigh fading channel by changing the period of a portion of the subcarriers utilizing QPSK in OFDM regulation. The representation of outputs is finished through MATLAB programming.

**Keywords**—OFDM System, Channel Estimation, Fading, BER.

## I. INTRODUCTION

OFDM is a strategy for encoding advanced data on multiple messenger frequencies. COFDM remains for Coded orthogonal frequency division multiplexing. It difference from OFDM on the grounds that in COFDM, forward blunder redress is attach to the flag before transmission. This is done to conquer mistakes. OFDM is orthogonal frequency division multiplexing (OFDM) method employ as a further multi-transporter adjustment strategy. An expansive number of firmly separated orthogonal sub-transporter signals are utilized to convey data on a few parallel information streams or channels.

The essential preferred standpoint of OFDM over single-transporter plans is its capacity to adapt to serious channel conditions without complex evening out channels. The low image rate makes the utilization of a watch interim between images moderate, making it conceivable to dispose of inter symbol impedance (ISI) and use echoes.

## II. RELATED WORK

**A. Zhong Fan, Georgios Kalogridis, Costas Efthymiou, Mahesh Sooriyabandara, Mutsumu, 2016**

This paper informs around a part of the problem and possibility of interchanges explore in the territory of shrewd frameworks and brilliant metering. Unmistakably the correspondences inquire about group has been currently looking for the „next huge thing“ after interests in late hotly debated issues, for example, subjective radio, agreeable interchanges, and MIMO have pretty much topped. I view that the new activity on keen framework overall gives a perfect possibility to correspondence and systems administration scientists to apply unique existing advances and also imagining new ones in this energizing region [12].

**B. PAN Pei-sheng, ZHENG Bao-yu, 2015**

Different information several yield (MIMO) frameworks can be combine with orthogonal recurrence division multiplexing (OFDM) frameworks to enhance the restricted and nature of remote interchanges. In this article, a direct estimation procedure in both space and recurrence area for MIMO-OFDM frameworks is proposed. It is indicate that the proposed conspire with space-recurrence pilot tones accomplish ideal least mean square mistake (MMSE) channel evaluation. Reproduction comes about show that the proposed strategy accomplishes great execution related to their input data streams [13].

**C. Muquet and M. de Courville, 2014**

This paper shows two new visually impaired channel recognizable proof strategies suited to multicarrier

framework (OFDM) misusing the excess presented by the adjunction of a cyclic prefix at the producer and depending on the assessment of the desired flag autocorrelation network are displayed. The proposed calculations can recognize any channel with no requirement on their zeroes area (counting non-least stage channels) and are hearty to the expansion of repetitive sound. Additionally a further improvement of the estimation exactness can undoubtedly be accomplished by exploiting officially introduce preparing images in current frameworks working in a semi-dazzle setting. Moreover one of the two recognizable proof methodologies has a low arithmetical many-sided quality which makes it especially alluring by and by. Notice that these strategies are not restricted to accepted DFT-type modulators and still employ with any immaculate recreation modulator [14].

### III. PROBLEM STATEMENT AND PROPOSED METHODOLOGY

#### A Problem Statement

Interference and fading are the superior performance depreciate factors in wireless communications. To enhance and affirm the framework's viability to oppose fading, displaying and reproduction of correspondence framework under fading channel is of incredible importance in the outline of correspondence framework. The normal for fading channel for various proliferation conditions is different and complex. Another complication lies in the viability of hostile to obstruction innovations. OFDM is multi-carrier scheme for remote correspondence because of its tendency of strong immunity from impedance and high spectra productivity, high information rate transmission. Channel analysis process can be separate into two parts: daze channel analysis and pilot-helped channel analysis. The station assessment strategies contemplated in the exposition are all pilot-helped, for pilot-supported station assessment are more appropriate in quick fading recurrence specific radio spread channel. A diverse pilot addition design brings about discrete BER exhibitions. 2-D pilot channel estimation is demonstrated to have better execution looking at than 1-D pilot channel estimation.

#### B Proposed Methodology

- Characterize the basic standard of OFDM system and ability to decrease ISI and ICI caused by single base band signal way. Change designs is similarly familiar and examined with more Right off the bat depict typical for darkening in remote correspondence especially Rayleigh clouding and AWGN channel amplify the achievement of OFDM system.

- Right off the bat depict typical for darkening in remote correspondence especially Rayleigh clouding and AWGN channel.
- Prompt Pilot-bolstered channel estimation frameworks to address little scale clouding issue in remote exchanges. Two 1-D pilot configuration, piece sort and brush sort, are look. Rectangular 2-D pilot outline, which is more fitting in repeat specific and time-variety clouding channel, is permitted and gage.
- Determine BER execution of OFDM arrangement underneath Rayleigh fading medium and AWGN medium and find out efficiency of employ 2-D pilot channel analysis to OFDM arrangement.

### IV. SYSTEM ARCHITECTURE

In OFDM, Forward Error Control/Correction (FEC) coding and interleaving are joined in the OFDM framework to accomplish the strength, required to ensure against burst mistakes. An OFDM framework with expansion of channel coding and interleaving is relegate to as Coded OFDM (COFDM). In a computerized space, parallel information is a massing and FEC coded with plans like convolution codes.




Fig.1.1: OFDM Transceiver System

The coded bit stream is interleaved to get to decent variety pick up. A while later, a blend of channel coded bits is related together (i. e. 1 for BPSK, 2 for QPSK, 4 for QPSK, and so on.) and mapped to comparing star grouping focuses. Now, the information is characterized in complex numbers and they are in serial. A serial to parallel converter is utilized and the IFFT operation is executing on the parallel complex information. The different data is coordinate together once more, specified by the number of approve transmission subcarriers. Cyclic prefix comprises each part of data as per the framework confirmation and the data is multiplexing in serial form. To transform across time area electronic information to time space basic information a Digital to analog transform is used. Accomplish RF regulation and swap across the signal to transmission frequency. Afterwards the transference of

signal from the transmitter recuing wire, the signs go across all the peculiarity and antagonistic vibe of remote channel. At the season of down-change of desired signal, transporter recurrence synchronization is actualizing. After employ the demodulated pilots ADC transformation, image timing synchronization is procured. A FFT is employ to demodulate the OFDM signal. From that extent onward, channel evaluation is really. The complex desired information is desired utilizing the estimation which is damped relating to the transmission heavenly body graph. FEC unravelling and interleaving are connected to recoup the initially transmitted piece stream.

## V. CHANNEL ESTIMATION

Radio signal transmitted through the remote divert in versatile correspondence. In remote correspondence radio signal experienced time scattering and recurrence scattering caused by multipath propagation and Doppler move, in this way, diminish the performance of the resemblance framework. OFDM framework can fundamentally diminish the impact of multipath fading, OFDM signal is effortlessly influenced by Doppler move, since Doppler move is identified with recurrence balance and abatement the orthogonality of OFDM sub-bearers. Channel estimation is technique to minimize fading and difficulty in OFDM framework by identifying the recurrence reaction of the fading channel.

## VI. EXPERIMENTAL RESULTS

The tabular representation of simulation parameter utilization for the system is shown below.

No. of bits transmitted = 10000

No. of carriers used = 6

Bits per each carrier = 1000

Spacing between the each carrier = 6 KHz

Carrier frequencies are used as 6 KHz for BPSK, QPSK modulation techniques.

TABLE.I: SIMULATION PARAMETER

Channel Model	Raleigh and AWGN Fading Channel
Modulation	16 QPSK
Noise	AWGN
Detector	ML Detector
Technique used	FFT and IFFT (Single Impulse)
Separation Distance	1/2
Antenna transmitting power	Equally
FFT size	128 samples per frames

Length of Guard Interval	22
Total symbol length with guard interval	150
Bits per each carrier	1000

The graphical representation of BER calculation of AWGN channel and Rayleigh fading channel is shown below




Fig 5.16 Comparisons between BER Calculations for AWGN and Rayleigh curve

## VII. CONCLUSION

We have considered a more reasonable channel show for impromptu systems, considering genuine channel impacts, for example, multipath. We have picked a Rayleigh fading model to catch the impacts of the multipath. A correlation of the execution of a specially appointed system working in a Rayleigh fading channel with the all the more usually utilized as a part of range channel demonstrate has demonstrated that the correspondence term versatility metric is defective for depicting the execution of the Rayleigh fading channel display for most uses of intrigue. We have presented the connection proportion as a more fitting execution metric which gives a more natural sign of connection accessibility (in a general sense) in specially appointed systems working in a Rayleigh fading channel condition. We will build up this work utilizing a more advanced model for the Rayleigh fading channel. Distinctive portability models will be considered for the development of the hubs to decide the viability of the connection proportion as versatility metric over a capacity of adaptability design.

## REFERENCES

- [1] Kandarpa Kumar Sarma, "MIMO Channel Modeling using Temporal Artificial Neural Network (ANN) Architectures", IITM'10, December 28-30, 2010, Allahabad, UP, India, pp 37-44, 2010.

- [2] Hussein Hijazi," Joint Data QR-Detection and Kalman Estimation for OFDM Time -Varying Rayleigh Channel Complex Gains", IEEE TRANSACTIONS ON COMMUNICATIONS 0090-6778/10@ 2010 IEEE Jin Whan Kang (2011)," Adaptive Modulation and Coding for MIMO- OFDM Systems using LMS Channel Prediction and CQI Table Adaptation", ICUIMC "11 February 21–23, 2011, Seoul, Korea.
- [3] Jin Whan Kang," Adaptive Modulation and Coding for MIMO-OFDM Systems using LMS Channel Prediction and CQI Table Adaptation", ICUIMC "11 February 21–23, 2016, Seoul, Korea.
- [4] M. Borgmann and H. Bölcskei, "Interpolation-Based Efficient Matrix Inversion for MIMO- OFDM receivers," Proc. 38th Asilomar Conf. Signals, Syst., and Computers, Pacific Grove, CA, Nov. 2004, pp. 1941–47.
- [5] Y. Li and G. L. Stüber, Orthogonal Frequency Division Multiplexing for Wireless Communications. Atlanta, GA: Georgia Inst. Technol., 2016.
- [6] S. Thoen, L. Van der Perre, M. Engels, and H. De Man, "Adaptive loading for OFDM/SDMA-based wireless networks," IEEE Trans. Commun., vol. 50, no. 11, pp. 1798– 1810, Nov. 2012.
- [7] B. Muquet and M. de Courville, "Blind and semi blind channel identification methods using second-order statistics for OFDM systems," in Proc. IEEE Int. Conf. Acoust., Speech, Signal Process., Mar. 2017, vol. 5, pp. 2745–2748.
- [8] Jaechan Lim," Inter-Carrier Interference Estimation in OFDM Systems With Unknown Noise Distributions", IEEE SIGNAL PROCESSING LETTERS 1070-9908 © 2009 IEEE
- [9] Van Nee, Richard, and Ramjee Prasad. OFDM for Wireless Multimedia Communications. Boston: Artech House, 2000.00
- [10] Wang, Zhengdao, and Georgios B. Giannakis. "Wireless Multicarrier Communications." IEEE Signal Processing Magazine (May, 2000): 29-48
- [11] Weinstein, S. and Ebert, P., "Data Transmission by Frequency Division Multiplexing using the Discrete Fourier Transform." IEEE Transaction Communication Technology. vol. COM-19, (October 2016): pp. 628-634.
- [12] C. Efthymiou, G. Kalogridis, Z. Fan, "The new frontier of communications research: smart grid and smartmetering", 1st International Conference on Energy-Efficient Computing and Networking, USA, 2016.
- [13] PAN Pei-sheng, ZHENG Bao-yu —Channel estimation in space and frequency domain for MIMO-OFDM systems| ELSEVIER journal of China Universities of Posts and Telecommunications, Vol. 16, No. 3, June 2009, Pages 40– 44.
- [14] B. Muquet and M. de Courville, "Blind and semi blind channel identification methods using second-order statistics for OFDM systems," in Proc. IEEE Int. Conf. Acoust., Speech, Signal Process., Mar. 2017, vol. 5, pp. 2745–2748.
- [15] Siavash M. Alamouti—A Simple Transmit diversity Technique for W ireless Communi-cations|, IEEE Journal on Select Areas in Communications, Vol. 16, No. 8, October 1998.
- [16] Heung-Gyoon Ryu, Yingshan Li, and Jin-Soo Park —An Improved ICI Reduction Method in OFDM Communication System| 2005.
- [17] Jianqiang He," MMSE Interference Suppression in MIMO Frequency Selective and Time - Varying Fading Channels", IEEE TRANSACTIONS ON SIGNAL PROCESSING 1053-587X © 2008 IEEE
- [18] Shih-Kang Wang e OFDM Systems", 978-1-4244-2309-5/09©2009 IEEE
- [19] Mitalee Agrawal," BER Analysis of MIMO OFDM System for AW GN & Rayleigh Fading Channel", International Journal of Computer Applications (0975 – 8887) , Volume 34– No.9, November 2017, pp 33-37.
- [20] Pollet, T., Van Bladel, M. and Moeneclaey, M., "BER Sensitivity of OFDM Systems to Carrier Frequency Offset and Wiener Phase Noise", IEEE transactions on communications. Vol. 43, No. 2/3/4, February/March/April 2013, pp 191-193.
- [21] M. Pukkila, "Channel Estimation Modeling", 2010
- [22] Rappaport, T., Wireless Communication: Principles and Practice. New Jersey: Prentice Hall, 1996.
- [23] Mosen, P.: „Adaptive Equalization of the Slow Fading Channel“, IEEE Trans., Aug 1974, IT-22, pp. 1064-1075
- [24] Bello, P. A., "Selective Fading limitations of the KATHRYN modem and some system design considerations." IEEE Transaction Communication Technology. vol.COM-13, (2017): pp. 320-333.
- [25] Moon, JAe Kyoung and Choi, Song In., "Performance of channel estimation methods for OFDM systems in multipath fading channels." IEEE Transaction on Communication Electronics. vol.46, (February 2017): pp. 161-170.
- [26] Zhao, Y. and Häggman, S.G., "Sensitivity to Doppler Shift and Carrier Frequency Errors in OFDM Systems-The Consequences and Solutions", IEEE conference proceedings VTC, pp. 2474-2478, 2016.
- [27] Ziv, J.: „Probability of decoding error for random phase and Rayleigh fading channels“, IEEE Trans., Jan 2017, IT-11, pp. 53- 61



- 
- [28] Cai, Xiaodong and Giannakis, Georgios B., "Error Probability Minimizing Pilots for OFDM with M-PSK Modulation over Rayleigh-Fading Channels." IEEE Transaction. Vehicular Technology. vol. 53, no.1, (January 2014): pp. 146-145.
  - [29] I. E. Telatar and D. N. C. Tse, "Capacity and Mutual Information of Wideband Multipath Fading Channels," IEEE Trans. Info. Theory, vol. 46, no. 4, July 2015, pp. 1384–14
  - [30] Hussein Hijazi (2008)," OFDM High Speed Channel Complex Gains Estimation Using KalmanFilter and QRDdetector", 978-1-4244-2489-4/08@ 2017 IEEE.
  - [31] Keller, Thomas, and Lajos Hanzo. "Adaptive Multicarrier Modulation: A Convenient Framework for Time-Frequency Processing in Wireless Communications." IEEE Proceedings of the IEEE 88 (May, 2000): 609-640
  - [32] Bingham, John A. C. "Multicarrier Modulation for Data Transmission: An Idea Whose Time Has Come." IEEE Communications Magazine (May, 2016): 5-14
  - [33] Li, Y., Seshadri, N. and Ariyavisitakul, S., "Channel Estimation for OFDM systems with transmitter diversity in mobile wireless channels." IEEE J. Select. Areas Communication (March 2015): pp. 461-470
  - [34] Tufvesson, F. and Hoeher, P., "Channel Estimation using Superimposed pilot Sequences,"IEEE Trans. Communication (March 2014).
  - [35] Tufvesson, F., Faulkner, M., Hoeher, P. and Edfors, O., "OFDM Time and Frequency Synchronization by spread spectrum pilot technique." 8th IEEE Communication Theory Mini Conference in conjunction to ICC'99, Vancouver, Canada, (June 2017): pp. 115- 119.
  - [36] Li, Y., "Pilot-symbol-aided channel estimation for OFDM in wireless systems." IEEE Transaction Vehicular Technology. vol. 49, no. 4,(Jul. 2017).
  - [37] CROZIER, S., FALCONER, D., and MAHMOUD, S.,,Shortblock equalization techniques employing channel estimation for fading time dispersive channels". IEEE Vehicular Technology Conference, May 2016, pp.142-146
  - [38] Torrance, J., and Hanzo, L., "Comparative study of pilot symbol assisted modem systems." Proceedings of IEEE conference on Radio Receivers and Associated Systems, Bath UK, (September 2016): pp. 36-41.